


TECHNICAL DATA SHEET • SPECIFICATIONS

FIRE-RATED INSULATED ACCESS DOOR WITH EXPOSED FLANGE Self-latching tool-key operated slam latch, piano hinge, stainless steel 304

PFI-SS3-00

INSTALLATION

Technical drawing PFI-SS3-00




Authorities Having Jurisdiction (AHJ) should be consulted in all cases as to the particular requirements that apply to the installation and use of fire-rated access doors.

STANDARD DIMENSIONS AND APPEARANCE

Dimensions • W X H		Number of locks	Weight	
inches	mm		lbs	KG
8 x 8	203 x 203	1	6.7	3.0
10 x 10	254 x 254	1	8.7	4.0
12 x 12	304 x 304	1	11.0	5.0
14 x 14	355 x 355	1	13.4	6.1
16 x 16	406 x 406	1	15.6	7.1
18 x 18	457 x 457	1	18.8	8.5
22 x 22	558 x 558	1	25.4	11.5
22 x 30	558 x 762	1	31.9	14.5
22 x 36	558 x 914	2	38.2	17.3
24 x 24	609 x 609	1	28.7	13.0
24 x 36	609 x 914	2	40.6	18.4
*24 x 48	609 x 1219	2	50.2	22.8
*30 x 30	762 x 762	1	40.5	18.4
*32 x 32	812 x 812	2	40.5	18.4
*36 x 36	914 x 914	2	54.5	24.7
*48 x 48	1219 x 1219	2	84.6	38.4

Your odd sizes: Made in 5 days

Rough floor opening is door size + 1/4" or + 6 mm



PROJET DATA

Project:	Date:	QTY	W	H
Architech:				
Dealer:				
Contractor:				
Location:				

DESCRIPTION AND MATERIAL SPECIFICATION

Material	20-gauge stainless steel 304 #4 door and 16-gauge stainless steel 304 #4 frame
Hinge	Continuous piano hinge, located on the second dimension (height)
Lock / Latch	Self-latching tool-key-operated slam latch and/or ring-operated slam latch, both included
Finish	#4 (Brushed finish)
Packaging	Individually wrapped, 1 door per box
Insulation	2" thick fire-rated mineral wool
Inside panel release	Mechanisms to allow panels to open from inside, standard on all doors over 12" x 12"

POPULAR OPTIONS

For complete list of options go to cendrex.com

Lock / Latch	Key-operated cylinder cam latch (-10), mortise deadbolt lock (-40, cylinder optional), mortise slam latch (-85, cylinder optional)
Handle	Fixed 4" handle (-21), 4" handle-operated slam latch (-22)
Other	Neoprene gasket (-60), masonry anchors (-240)

For vertical use

Certified to standards: UL 10B (2008) (R2020), NFPA 252 (2022), CAN/ULC S104 (2015) (R2020)
Rating achieved: 3 hours, neutral/negative pressure

Maximum size: 48" wide x 48" high (1,219 mm x 1,219 mm). Maximum area of 2,304 in². Tolerance on height and width limitation is ± 3" (76 mm) as long as the area does not exceed 2,304 in².

Temperature rise: 450°F (232°C) after 30 min.

OPTIONS

This comprehensive list includes all available options. Please consult our catalog or contact our customer service to verify the feasibility of your chosen combination.

LOW SECURITY LOCKING MECHANISM



- ☐ **35**
Screwdriver operated
cam latch



- ☐ **220**
Screwdriver operated
cylinder Cam latch



- ☐ **80**
Ring/tool key operated slam
latch



- ☐ **55**
Hex head slam latch and ring key
operated slam latch



- ☐ **30**
Slide latch



- ☐ **50**
Allen hex head cam latch

HANDLES



- ☐ **25**
WITH KEY - 4" handle and key
operated cam latch



- ☐ **100K**
Key-operated recessed handle
cam latch with cap over key
path



- ☐ **20**
WITHOUT KEY - 4" handle
operated cam latch



- ☐ **22**
WITHOUT KEY - 4" handle
operated slam latch



- ☐ **21**
WITHOUT KEY
Fixed 4" handle



- ☐ **26**
WITHOUT KEY - L handle

MEDIUM SECURITY LOCKING MECHANISM



- ☐ **10**
Key-operated cylinder
cam latch



- ☐ **15**
Mortise cam latch preparation
15C
Mortise cam latch preparation,
keyed differently
15CKA
Mortise cam latch preparation,
keyed alike



- ☐ **85**
Mortise slam latch



- ☐ **85C**
Mortise slam latch with cylinder
85CKA
Mortise slam latch cylinder
keyed alike



- ☐ **90**
Pinned hex head cam latch



- ☐ **C**
Cylinder cam latch,
keyed differently



- ☐ **CKA**
Cylinder cam latch,
keyed alike

MATERIALS



- ☐ **GS**
Galvanneal steel



- ☐ **AL**
Aluminum



- ☐ **SS**
Stainless steel



- ☐ **CR**
Cold rolled steel

HIGH SECURITY LOCKING MECHANISM



- ☐ **40**
Mortise deadbolt lock



- ☐ **40C**
Mortise Deadbolt Lock with
Cylinder, keyed differently



- ☐ **40CKA**
Mortise deadbolt lock with
cylinder, keyed alike



- ☐ **99**
Inside release thumbturn for
mortise deadbolt lock



- ☐ **45**
Mortise preparation for
detention deadbolt lock



- ☐ **46**
Detention deadbolt lock



- ☐ **47**
CIDetention deadbolt Key

OTHERS



- ☐ **60**
Gasket



- ☐ **160**
Holding cable



- ☐ **240**
Masonry anchors